



SMART ACRYLIC EPOXY COATING

TECHNICAL INFORMATION SHEET

- (1) THIS PRODUCT IS NON- HAZARDOUS ACCORDING TO THE CRITERIA OF WORKSAFE AUSTRALIA.
- (2) THIS IS A TWO PART ACRYLIC EPOXY COATING (NON-SACRIFICIAL) FOR ANY SURFACE
- (3) PREPARATION: MAKE SURE ALL PAINTED SURFACES ARE CLEAN & FREE OF ANY CONTAMINATION.UNPAINTED BRICK SURFACES TO BE WASHED WITH SMART WALL WASH AND ALLOWED TO DRY COMPLETELY BEFORE APPLICATION OF THIS PRODUCT TO ENSURE ANY REMNANTS OF SURFACTANTS, LIME,GRAFFITI REMOVAL CHEMICALS OR OTHER CONTAMINANTS WHICH WILL EFFECT THE ADHERANCE OF THE ACRYLIC EPOXY COATING TO THE BRICK OR CONCRETE SURFACE ARE REMOVED
- (4) APPLICATION : MIX 3 LITRES PART A AND ONE LITRE PART B FOR 3 MINUTES AND ALLOW TO STAND FOR 10 MINUTES BEFORE APPLICATION.THEN RE-STIR TO ENSURE AN EVEN MIX.**(IMPORTANT TO NOTE THAT ONCE MIXED YOU HAVE A LIFE OF 2 HOURS ONLY.IF USED AFTER THIS TIME THE COATING MAY BECOME MILKY IF APPLIED)** THE FIRST COAT SHOULD BE APPLIED WITH A ROLLER OR BRUSH AND ALLOW TO BECOME TACK DRY (IN COOL WEATHER THIS MAY BE UP TO 4 HOURS) APPLY SECOND COAT AFTER 4- 6 HOURS –BUT NO LONGER!
- (5) SMART ACRYLIC EPOXY COATING CURES WITHIN 24 HOURS. GRAFFITI MAY THEN BE REMOVED USING SMART ERAZE GRAFFITI REMOVER AND THEN WASHING SURFACE DOWN WITH WATER.
- (6) SPREAD RATE- AVERAGE 8 SQUARE METRES/LITRE.
- (7) CLEAN UP EQUIPMENT IN WATER AND SMART GENERAL PURPOSE DETERGENT IF REQUIRED.
- (8) IMPORTANT INFORMATION:IF THE PRODUCT IS NOT APPLIED AS ABOVE THEN PRODUCT BECOMES INEFFECTIVE.
- (9) **THE PRODUCT MUST BE USED WITHIN 2 HOURS OF BEING MIXED.ANY REMAINING MUST BE DISPOSED OF AFTER THIS TIME AS IT WILL TURN MILKY WHITE IF APPLIED TO ANY SURFACE.**
- (10) PRIOR TO THE COMMENCEMENT OF ANY WORKS CONTACT THE SUPPLIER SMART DISTRIBUTION SERVICES ON 03 94598990 IF YOU ARE UNSURE AND REQUIRE INSTRUCTION.